


# F3 7.0

## SPECIFICATIONS

WEIGHT	♣ 12.8 kg ♣ 13.0 kg
SIZES	♣ 50-54-57-60-63cm ♣ 47-50-53-56-59cm
COLOUR	Geyser
FRAME	Super smooth welded frame. Triple-buttet hydroformed aluminium tubes. Down tube with internal shifter and brake cables, tapered headtube with integrated 1 1/8"/1 1/4" headset, integrated rear carrier and mudguard attachment and replaceable rear derailleur hanger.
FRONT FORK	KOGA full carbon for Disc brake with integrated headlight and mudguard attachment
HEADSET	Industrial bearing - Integrated in frame
HANDLEBAR	KOGA Riser Oversized alloy
STEM	KOGA rigid Oversized - Lightweight alloy
HANDLEBAR TAPE/GRIPS	KOGA Comfort
DISC-/HYDRAULIC BRAKE SET (F)	Shimano Deore XT T8000 hydraulic disc brake, IS mount type
DISC-/HYDRAULIC BRAKE SET (R)	Shimano Deore XT T8000 hydraulic disc brake, post mount type
ROTOR FRONT	Shimano RT-70 160mm
ROTOR REAR	Shimano RT-70 160mm
SHIFT LEVER (R)	Shimano Deore XT T8000
SHIFT LEVER (L)	Shimano Deore XT T8000
CHAIN	KMC X10EL
CRANK SET	Shimano Deore XT T8000 48-36-26T for 10-speed
BOTTOM BRACKET	Shimano BSA
CASSETTE	Shimano HG-81 10 speed - 11-32T
REAR DERAILLEUR	Shimano Deore XT T8000 10-speed
FRONT DERAILLEUR	Shimano Deore XT T8000 for 3x11-speed
FRONT HUB	Shimano Dynamo Hub Deore XT T8000 Disc
REAR HUB	Shimano Deore XT M8000 Disc
TIRE (F)	Schwalbe Marathon Racer 40-622
TIRE (R)	Schwalbe Marathon Racer 40-622
TUBE	Schwalbe ExtraLight
RIM (F)	Mach1 560 Disc
RIM (R)	Mach1 560 Disc
SPOKES F1	Mach1 Pro
SADDLE	Fizik Rondine
SEAT POST	KOGA alloy 27,2mm
MUDGUARD (F)	KOGA 46 mm
MUDGUARD (R)	KOGA 46 mm
HEADLIGHT	B&M Eyc 50 Lux
REAR LIGHT	Spanninga Plateo
REAR CARRIER	Racktime frame integrated
KICKSTAND	Atran Velo Move
BELL	Witek Compact
PEDALS	KOGA Sole-Mate
PUMP	KOGA Telescopic



## GEOMETRY

### ♣ GENTS

SIZE	T/T	C/S	WB	BB	RA	H/T°	S/T°	TR	H/T	RE	ST
50	575	457	1074	55	45	70,5	72,0	75	115	389	572
54	590	457	1067	55	45	71,5	71,0	68	135	385	595
57	605	457	1082	55	45	71,5	71,0	68	155	394	614
60	620	457	1097	55	45	71,5	71,0	68	180	400	638
63	635	457	1112	55	45	71,5	71,0	68	210	405	667

### ♣ MIXED

SIZE	T/T	C/S	WB	BB	RA	H/T°	S/T°	TR	H/T	RE	ST
47	566	457	1065	55	45	70,5	72,0	75	145	371	601
50	573	457	1073	55	45	70,5	72,0	75	155	375	610
53	580	457	1080	55	45	70,5	72,0	75	165	379	619
56	587	457	1064	55	45	71,5	71,0	68	175	369	633
59	594	457	1070	55	45	71,5	71,0	68	185	373	643